

# KONTROLDRY®

Eliminates Rising Humidity

## TECHNICAL DATA SHEET

### DIMENSIONS

Width 180 mm - Height 180 mm - Depth 50 mm

### MODELS

Model 10-R06 (range of 6 meters approx.)

Model 10-R09 (range of 9 meters approx.)

Model 20-R12 (range of 12 meters approx.)

Model 20-R15 (range of 15 meters approx.)

Model 20-R20 (range of 20 meters approx.)

### TECHNICAL DATA

Power supply 110/240 Vac - 50/60 Hz 4 VA

In alternative or in contemporary 10/14 Vdc

Backup power supply by internal backup batteries

Consumption 4 Wh approx

Class II insulation according to CEI EN 60335-1 (1998) standard

Degree of protection IP40

Action Range 6 - 20 meters depending on the model

Weight 780g

CE Mark of **KontrolDRY**® device conformity with EEC Directive 73/23 (electrical products safety) and 89/336 (electromagnetic compatibility)

TÜV ITALY SAFETY CERTIFICATIONS HUMAN EXPOSURE SECURITY  
ELECTROMAGNETIC FIELDS

Conformity with CEI EN 62233 (2008) standard

Electric field strength 0.3 V / m

TÜV ITALY CERTIFICATIONS ON SECURITY, EMISSIONS AND IMMUNITIES

Conformity with CEI EN 60335-1 (2002) standard

Conformity with CEI EN 55011 (2009) - CEI EN 61000-6- 3 (2007)

Conformity with CEI EN 61000-3-2 (2007) - CEI EN 61000-3- 3 (2009)

CEI EN 61000-4-2 (1996) - CEI EN 61000-4-3 (2007)

CEI EN 61000-4- 4 (2006) - CEI EN 61000-4- 5 (2007)

CEI EN 61000-4-6 (2009) - CEI EN 61000-4-8 (1997)

CEI EN 61000-4-11 (2006) - CEI EN 61000-6-2 (2006)

